

CANADA SENSORS TECHNOLOGY INC.



Manufacturer of Advanced Technology Pressure & Level Transmitters

CRN Approval, ISO 9001:2015 Certified



PRESSURE TRANSMITTER – PROCESS 6

Non-Incendive Model, General Purpose for High Pressure

Canada Sensors Technology Inc. offers an affordable solution with the Process 6 Pressure Transmitter without sacrificing quality or longevity of use.

FEATURES

- ✓ Non-incendive for Class I, Div. 2, Zone 2 Hazardous Locations for High Pressure
- ✓ 4 – 20 mA Two Wire, Voltage, MODbus, CANbus, J1939
- ✓ 0.25% BSL Accuracy
- ✓ Monolithic Block Glass Bonded One Piece Stainless Steel Machined Sensor
- ✓ No Welded Diaphragms, No Internal O-rings, No Silicone Oil Fill
- ✓ Single seal compliant to ANSI/ISA-12.27.01.2003
- ✓ Zero & Span Function
- ✓ >100 million Cycles
- ✓ Pressure Ranges 15,000 PSI, 20,000 PSI, 30,000 PSI
- ✓ Heavy Duty 316SS Powder Coated Canister
- ✓ Temperature Compensated 0C to +50C
- ✓ Maximum Operating Temperature -40C to +95C
- ✓ Ingress Protection IP67
- ✓ Multiple Electrical Connectors & Housings Available
- ✓ Autoclave ¼" F250C Process Connection (17-4phSs or 316SS)
- ✓ Laser Engraved Product Information
- ✓ RoHS2 Compliant
- ✓ 2 Year Conditional Warranty (Serial Number Traceability)
- ✓ Unparalleled Value



Contact Us:

Canada Sensors Technology Inc.

10 – 328 Wale Road
Victoria, BC V9B 0J6
Canada
250-588-8085

sales@canadasensors.com
www.canadasensors.com

Manufacturer of Advanced Technology
Level and Pressure Transmitters



MISSION STATEMENT

Canada Sensors Technology Inc. strives to build a mutually positive and beneficial relationship with our customers, ensuring their long-term success, through the understanding of their needs and the needs of their customers.

We will listen to our customers and constantly improve our technologies as our customers' needs change with time.

Canada Sensors Technology Inc. is committed to providing the highest level of product quality and customer service. Canada Sensors Technology Inc. is ISO 9001:2015 certified.

Technical Specifications - Process 6

Performance

| | |
|------------------------|-------------------------------|
| Accuracy: | 0.25% Full Scale Output |
| Stability: | < 0.1% Full Scale Output/Year |
| Temperature Range: | -40C to +95C |
| Temperature Accuracy: | 1% Full Scale Output @ +50C |
| Pressure Cycles: | > 100 Million |
| Over Range Protection: | 2 x Full Scale Output |
| Burst Pressure: | 5 x Full Scale Output |

NOTE: Over Range Protection and Burst Pressure shall be reduced to 1.5 x Full Scale Output for pressures exceeding 10,000 PSI due to thread limitations

Electrical Data

| | |
|---|---|
| Excitation: | 10 - 28 VDC (product accessories may alter excitation values) |
| Comms: | 4-20 mA, 0-5 VDC or 0-10 VDC or Ratio Metric, RS485-Modbus, CANopen, J939 |
| Current Consumption: | 5 mA |
| Zero Offset: | 0.5% Full Scale Output set by Customer |
| Span Tolerance: | 0.5% Full Scale Output set by Customer |
| Output Load: | 9 Volts typical @ 24 VDC 750 OHMS |
| Non-incendive for Zone 2 Division 2 Hazardous Locations | |

NOTE: An Ex Barrier is required for any connections that cross the boundary from an Ordinary Location (Non-Classified/Non-Hazardous) to a Classified (Hazardous) location

Environmental Data

Temperature

| | |
|------------|--|
| Operating: | -40C to +95C (product accessories may alter temperature ratings) |
| Storage: | -55C to +125C |

Thermal Limits

| | |
|--------------------|-----------------------------|
| Compensated Range: | 0 to +50C |
| Temp Comp Zero: | 1% Full Scale Output @ +50C |
| Temp Comp Span: | 1% Full Scale Output @ +50C |

Physical Data


| | |
|--|---|
| Sensor: | Monolithic Block: 17-4phSS or 316SS |
| Vibration: | 25gRMS from 20Hz to 2000Hz |
| Shock: | 100g , half sine, 11mSec. |
| Sensor: | Silicone Oil Filled NOT Available on this model |
| Vibration: | 25gRMS from 20Hz to 2000Hz |
| Shock: | 100g , half sine, 11mSec. |
| NOTE: Silicone Oil Filled Sensors are a factory option for low pressure | |
| Process Connection: | 1/4" F250C |
| NOTE: ANSI Regulations dictate that NPT Thread should not to exceed 8,000 PSI @ +125C | |
| Electrical Connection: | 316SS Thread-on 1/2" MNPT Solid Conduit Fitting or w/ Aluminum XP Heads; Bendix Twist 6 Pin (PTIH-10-6P); M12 |

NOTE: 316SS Wetted Parts are the minimum requirement for NACE compliance

Product Weights:

| | <u>OZ</u> | <u>LBS</u> | <u>KG</u> |
|--|-----------|------------|-----------|
| Process 6 w/ F250C Autoclave & 316SS Thread-on 1/2" MNPT Solid Conduit Fitting (2 ft Flying Lead) | 24.0 | 1.5 | 0.68 |
| Process 6 w/ F250C Autoclave & Bendix Twist 6 Pin (PTIH-10-6P); M12 | 15.0 | 0.9 | 0.43 |
| Process 6 w/ F250C Autoclave & Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting - Blank - No Window | 59.0 | 3.7 | 1.67 |
| Process 6 w/ F250C Autoclave & Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting w/ Digits LCD Loop Powered Display | 112.0 | 7.0 | 3.18 |

Process Connections:



1/4" F250C

Electrical Connections:



THREAD ON 1/2" MNPT



BENDIX TWIST CONNECTOR
6 PIN



M12

Product Accessories

- Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting - Blank - No Window
- Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting w/ 5 Digits LCD Loop Powered Display



Product Nomenclature

MODEL: Pressure Transmitter - Process 6

PN Example: A-B-C-D-E-F-G-H-I-J

06-01-03-01-034-09-02-12-02-02:

Process 6 Transmitter, 4-20 mA, Zero and Span, Gauge (PSIG), 0 - 20000 PSI, 1/4" F250C, 316SS Wetted Parts, 316SS Thread-on 1/2" MNPT Solid Conduit Fitting with 2 ft Flying Lead, No Treatment, 0.25% Accuracy

| | A | B | C | D | E | F | G | H | I | J |
|--------------------------------|-----|---|---|---|---|---|---|---|---|---|
| Model | 06 | - | Process 6 | | | | | | | |
| Output | 01 | - | 4-20 mA | | | | | | | |
| | 02 | - | 0-5 Volts | | | | | | | |
| | 03 | - | 0-10 Volts | | | | | | | |
| | 04 | - | RS485 – Modbus | | | | | | | |
| | 05 | - | CANopen | | | | | | | |
| | 06 | - | J1939 | | | | | | | |
| Calibration Adjustment | 03 | - | Zero and Span | | | | | | | |
| Pressure Reference | 01 | - | Gauge (PSIG) | | | | | | | |
| | 02 | - | Absolute (PSIA) | | | | | | | |
| | 03 | - | Sealed Gauge | | | | | | | |
| Pressure Range | 033 | - | 0 – 15000 PSI | | | | | | | |
| | 034 | - | 0 – 20000 PSI | | | | | | | |
| | 035 | - | 0 – 30000 PSI | | | | | | | |
| Process Connection | 09 | - | 1/4" F250C | | | | | | | |
| Wetted Parts | 01 | - | 17-4phSS | | | | | | | |
| | 02 | - | 316SS | | | | | | | |
| Electrical Connection | 12 | - | 316SS Thread-on 1/2" MNPT Solid Conduit Fitting (2 ft Flying Lead) | | | | | | | |
| | 13 | - | 316SS Thread-on 1/2" MNPT Solid Conduit Fitting (4 ft Flying Lead) | | | | | | | |
| | 14 | - | 316SS Thread-on 1/2" MNPT Solid Conduit Fitting (6 ft Flying Lead) | | | | | | | |
| | 15 | - | 316SS Thread-on 1/2" MNPT Solid Conduit Fitting (10 ft Flying Lead) | | | | | | | |
| | 31 | - | Bendix Twist Connector 6 Pin (PTIH-10-6P) | | | | | | | |
| | 32 | - | M12 | | | | | | | |
| | 36 | - | Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting - Blank - No Window | | | | | | | |
| | 42 | - | Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting w/ 5 Digits LCD Loop Powered Display | | | | | | | |
| Environmental Treatment | 02 | - | No Treatment | | | | | | | |
| | 04 | - | DLC (Diamond Like Coating) | | | | | | | |
| Accuracy | 02 | - | 0.25 % | | | | | | | |

E: Alternate Pressure Range Units

kPa

| | | | |
|-----|-----------|---|----------------|
| kPa | 033 - kPa | - | 0 - 100000 kPa |
| kPa | 034 - kPa | - | 0 - 140000 kPa |
| kPa | 035 - kPa | - | 0 - 200000 kPa |

mBar

| | | | |
|------|------------|---|------------------|
| mBar | 033 - mBar | - | 0 - 1000000 mBar |
| mBar | 034 - mBar | - | 0 - 1400000 mBar |
| mBar | 035 - mBar | - | 0 - 2000000 mBar |

mm Hg

| | | | |
|-------|-------------|---|-------------------|
| mm Hg | 033 - mm Hg | - | 0 - 800000 mm Hg |
| mm Hg | 034 - mm Hg | - | 0 - 1000000 mm Hg |
| mm Hg | 035 - mm Hg | - | 0 - 1500000 mm Hg |

in H₂O (60° F)

| | | | |
|-----------------------------|---------------------------|---|--|
| in H ₂ O (60° F) | 033 - in H ₂ O | - | 0 - 400000 in H ₂ O (60° F) |
| in H ₂ O (60° F) | 034 - in H ₂ O | - | 0 - 500000 in H ₂ O (60° F) |
| in H ₂ O (60° F) | 035 - in H ₂ O | - | 0 - 800000 in H ₂ O (60° F) |

mm H₂O (4° C)

| | | | |
|----------------------------|---------------------------|---|---|
| mm H ₂ O (4° C) | 033 - mm H ₂ O | - | 0 - 10000000 mm H ₂ O (4° C) |
| mm H ₂ O (4° C) | 034 - mm H ₂ O | - | 0 - 14000000 mm H ₂ O (4° C) |
| mm H ₂ O (4° C) | 035 - mm H ₂ O | - | 0 - 20000000 mm H ₂ O (4° C) |

in Hg (32° F)

| | | | |
|---------------|-------------|---|-------------------------|
| in Hg (32° F) | 033 - in Hg | - | 0 - 30000 in Hg (32° F) |
| in Hg (32° F) | 034 - in Hg | - | 0 - 40000 in Hg (32° F) |
| in Hg (32° F) | 035 - in Hg | - | 0 - 60000 in Hg (32° F) |

Bar

| | | | |
|-----|-----------|---|--------------|
| Bar | 033 - Bar | - | 0 - 1000 Bar |
| Bar | 034 - Bar | - | 0 - 1400 Bar |
| Bar | 035 - Bar | - | 0 - 2000 Bar |

ata (kg/cm²)

| | | | |
|---------------------------|-----------|---|------------------------------------|
| ata (kg/cm ²) | 033 - ata | - | 0 - 1000 ata (kg/cm ²) |
| ata (kg/cm ²) | 034 - ata | - | 0 - 1400 ata (kg/cm ²) |
| ata (kg/cm ²) | 035 - ata | - | 0 - 2100 ata (kg/cm ²) |